



LX 2000			
a.c. output	230 V	<sup>1</sup> max.kW	1,9
	50 Hz 1~	<sup>2</sup> cont.kW	1,5
power factor		cos ø	1
fuel		Gasoline	
starting		Recoil starter	
alternator		Synchronous	
engine		TECUMSEH GEOTEC 40G	
cooling system		air	
displacement	c.c.	172	
n° cylinders		1	
prime power	HP	3,3	
R.P.M.		3000	
fuel tank capacity	lt.	5	
<sup>3</sup> / <sub>4</sub> load operating hours	h	3,5	
sound power level <sup>3</sup>	L <sub>WA</sub>	95	
acoustic pressure at 7 mt.	dB(A)	70	



DIMENSIONS	L	495	mm
	W	315	mm
	H	425	mm
WEIGHT		31	kg

<sup>(1)</sup> **Stand-by power:**  
power available for emergency

<sup>(3)</sup> Homologation "Directive 2000/14/EC"

<sup>(2)</sup> **Prime power:** maximum power  
available at variable loads for an  
unlimited numbers of hours

**The unit is composed of the following components:**

- Recoil starter
- Generator running lamp
- Oil level warning device
- Thermal circuit breaker
- Shuko socket
- d.c. output 12V 15A